PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:		(11) International Publication Number:	WO 98/49019
B44D 3/00, B05C 21/00	A1	(43) International Publication Date:	5 November 1998 (05.11.98)

(21) International Application Number:

PCT/PL97/00023

(22) International Filing Date:

29 September 1997 (29.09.97)

(30) Priority Data:

P.319675

25 April 1997 (25.04.97)

PL

(71)(72) Applicant and Inventor: BUJNOWICZ, Michał [PL/PL]; ul. Bracka 33 m.60, PL-95-200 Pabianice (PL).

(74) Agent: FEDEROWICZ, Jadwiga; Al. Śmigłego-Rydza 29 m.11, PL-93-281 Łódź (PL).

(81) Designated States: CA, CN, CZ, HU, JP, NO, RU, SE, UA, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).


Published

With international search report. With amended claims.

(54) Title: DEVICE FOR CLEANING PAINT ROLLERS

(57) Abstract

The device is used to clean paint rollers after use, with the aid of water. It has a paint scraping segment (2) fixed to a handle (1). The segment (2) takes the form of part of a ring, and its inner surface (10) is arc-shaped. The radius of the arc is adapted to the diameter of a roller. In addition, the surface (10) is chamfered (13) on both sides. The segment (2) is fixed to the handle (1) in a fixed or removable manner, for example by means of a screw. On the outer side of the segment (2) there are further arc-shaped recesses (11 and 12); the radii of these are adapted to the dimensions of painting devices having small oval cross sections. A cleaning brush (3), which is used to clean those elements of painters' equipment that are difficult to reach, is fixed to the handle (1) on the opposite side to that which carries the segment (2).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	· SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑÜ	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Paso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JР	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DEVICE FOR CLEANING PAINT ROLLERS

The object of the invention is a device to clean painting rollers from a paint. Such rollers are a piece of equipment used to paint different surfaces.

Common devices used by painters are equipped with rotating rollers, whose coating on a stiff construction is made of textile fibres material which absorb liquids and are similar to woolfur, pure wool or elastic artificial materials similar to sponges.

The roller is used to pick up a suitable quantity of a paint from a container and next to cover with this paint - by means of the roller rotation - surfaces intended to be painted.

After painting, not to let the paint to dry out, the rollers are directly cleaned in manual way by means of squeezing and twisting off the outer, paint absorbing coating under a steam of warm water. Due to a direct contact of a person with a paint and frequent application of cold water, the cleaning is unpleasant and toilsome process. Different kinds of open-work or solid plates with convexities are known, e.g. according to the patent application no P 311 199, the plates are assigned to scrap an excessive amount of paint to uniformly distribute a suitable quantity of a paint on the roller before painting process of an intended surface.

Using multiple rubbing of the roller on the scraping plate, it is possible to remove under the pressure only a small quantity of the paint into the container. However it hardly influences on the shortening of the manual cleaning process under the water stream.

The aim of the invention is to design a device which could facilitate the cleaning of the painting rollers from a paint to reach high efficiency of cleaning with limited water waste. According to the invention, a device has been designed, which contains a paint scraping segment with an arc-shaped surface from the inner side, adjusted to the roller's diameter, fixed to the handle. Additionally, both sides of the arc-shaped surfaces are chamfered.

The scraping segment is fixed to the handle in stiff or in separable way. From the outer side it also has the arc-shaped recesses, adjusted to the cleaning elements of the painting devices with smaller oval cross-sections.

A cleaning brush is fixed to the handle from the other side of the segment.

The object of the invention is shown as an exemplary model in figures, where: fig. 1 represents

- 2 -

the device in a partial, longitudinal section, fig. 2 - magnified lower part of the device in separated position, in a vertical section, fig. 3 - lower part of the device in top view, fig. 4 - scraping segment of the device in top view, fig. 5 - the device with the painting roller and the cleaning device in working position, in a perspective top view.

The device consists of exchangeable scraping segments $\underline{2}$ and brush $\underline{3}$ fixed to the handle $\underline{1}$. The handle $\underline{1}$ is produced of steel rod of oval cross-section. In the upper part of the handle, on its straight or bent part there is placed a grip $\underline{4}$. In the lower part of the handle, the bent tip is ended with quadrangular pivot $\underline{5}$, in which, on the side there is a seat $\underline{6}$ for the screw $\underline{7}$ which fix the segment. There is a threaded hole $\underline{8}$ for screw $\underline{9}$ used to fix the brush $\underline{3}$ on the other side of the segment near to the bent area in the handle.

The segments $\underline{2}$ have on the inner side arc-shaped surfaces $\underline{10}$, adjusted to a diameter of the painting roller.

Additionally on the outer side, they have arc-shaped recesses <u>11</u> and <u>12</u> adjusted to clean the smaller elements with oval cross-section of the painting devices.

Particularly, the recess $\underline{11}$ is assigned to clean the handle rod, and recess $\underline{12}$ to clean a small roller, frequently used by professional painters.

The arc-shaped inner surfaces have on both sides chamfers 13 of the front edges, facilitating guiding of the device and removing of a paint during the roller cleaning process due to decreasing of the friction. The front edges of the recesses 11 and 12 also have the chamfers 14 and 15. In the middle part, the segment 2 has a seat 16 of quadrangular cross-section, adjusted to shape of a handle pivot. The best vertical bending angle for the seat is from 10° to 20°. It assures proper position of the handle 1 with relation to the segment and facilitates manipulation of the device during the roller cleaning process. From the side, in the middle of the seat 16, there is a threaded hole 17 connected to the seat, for the screw 7, which fix the segment to the handle. The segment 2 is a art of a ring, or profitably semi-ring and it is made of plastic or metal. The segment can be fixed to the handle in separable way by means of a simple screw connection, or other known connection solutions.

In extreme case, it can be fixed in stiff way.

In the presented example the handle and the segment are connected in separable way. Several exchangeable segments, adjusted to the diameters of painting rollers frequently used by professional painters are included into the set of the device.

WO 98/49019 PCT/PL97/00023 - 3 -

In order to obtain high efficiency of the roller cleaning, the scraping segment with inner diameter should be more or less equal to the outer diameter of the stiff part of the roller, where in most cases there is a coating made of textile fibres material which absorb liquids.

Holding the grip of the device with painting roller in one hand, placing the roller on scraping plate in a container with paint and holding the grip $\underline{4}$ in the other hand, the segment of the device is put on a soft coating of the roller.

Performing the plane movements along the roller, successively on its entire circumference and simultaneously exerting the pressure, the notable amount of paint is pulled down from the front surfaces by means of the segment, back into a container. Next, a precise cleaning of the roller is performed by a fast, hand made and back-and-forward movements along the roller, as it is shown in fig. 5. It can be done for example in a wash-bowl, under the steam of cold water. The side surfaces of the roller are cleaned by means of the brush 3, placed on the opposite side of the scraping segment, the handle rod is cleaned by means of putting it in smaller recess 11 of the segment. Usually, a brush is used to clean the elements of painters equipment which are hard to reach.

The device, according to the invention, eliminates usage of warm water during the cleaning process and simultaneously decrease usage of cold water with comparison to the traditional method which is based on manual cleaning by means of squeezing and twisting off the outer, paint absorbing coating under a steam of warm and/or cold water.

Claims


- 1. A device used to clean the painting rollers from a paint is characterised by a paint scraping segment ($\underline{2}$), which surface is arc-shaped from the inner side ($\underline{10}$), and by fixing to the handle ($\underline{1}$).
- 2. The device, according to the claim 1 is characterised by the scraping segment ($\underline{2}$) is fixed to the handle ($\underline{1}$) in stiff or in separable way and by having from the outer side arc-shaped recesses ($\underline{11}$ and $\underline{12}$), adjusted to the cleaning elements of the painting devices with smaller oval cross-sections.
- 3. The device, according to the claim 1 or 2 is characterised by the cleaning brush ($\underline{3}$) fixed to the handle ($\underline{1}$), from the other side of segment ($\underline{2}$) location.
- 4. The device, according to the claim 1 is characterised by the arc-shaped surface ($\underline{10}$) of the segment and by having chamfers ($\underline{13}$) from both sides.


AMENDED CLAIMS


[received by the International Bureau on 16 April 1998 (16.04.98); original claim 1 amended; remaining claims unchanged (1 page)]

- 1. A device used to clean the painting rollers from a paint is characterised by a paint it crosswise scraping segment ($\underline{2}$), which surface is arc-shaped from the inner side ($\underline{10}$), and by fixing to the handle ($\underline{1}$).
- 2. The device, according to the claim 1 is characterised by the scraping segment ($\underline{2}$) is fixed to the handle ($\underline{1}$) in stiff or in separable way and by having from the outer side arc-shaped recesses ($\underline{11}$ and $\underline{12}$), adjusted to the cleaning elements of the painting devices with smaller oval cross-sections.
- 3. The device, according to the claim 1 or 2 is characterised by the cleaning brush ($\underline{3}$) fixed to the handle ($\underline{1}$), from the other side of segment ($\underline{2}$) location.
- 4. The device, according to the claim 1 is characterised by the arc-shaped surface ($\underline{10}$) of the segment and by having chamfers ($\underline{13}$) from both sides.

WO 98/49019 PCT/PL97/00023







INTERNATIONAL SEARCH REPORT

Interr nal Application No PCT/PL 97/00023

			· · · · · · · · · · · · · · · · · · ·
A. CLASSI IPC 6	FICATION OF SUBJECT MATTER B44D3/00 B05C21/00		
According to	o International Patent Classification(IPC) or to both national classific	eation and IPC	-
	SEARCHED		
Minimum do	ocumentation searched (classification system followed by classification B44D 805C	on symbols)	
	tion searched other than minimum documentation to the extent that s		
Electronic a	ata base consulted during the international search (name of data ba	ise and, where practical, search terms used	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the rele	evant passages	Relevant to claim No.
Х	DE 93 00 198 U (W. NAGY) 18 March see page 2, line 5 - page 7, line		1,2
X	GB 2 270 464 A (L G HARRIS & CO I 16 March 1994 see page 1, paragraph 4 - page 5 paragraph 3	1	
X	FR 2 147 406 A (MOULINAGE ET RETO CHAVANOZ) 9 March 1973 see page 1, line 27 - page 4, lir	1,4	
х	US 5 546 625 A (E. H. MEALEY SR) 1996	1	
	see column 3, line 20 - column 4,	,	
	•	-/	
			·
انا ا	ner documents are listed in the continuation of box C.	X Patent family members are listed in	n annex.
*A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filling date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention filling date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filling date but later than the priority date claimed "E" document published prior to the international filling date but later than the priority date claimed "C" document given the document is taken alone with one or more other such documents is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "E" document published prior to the international filling date but later than the priority date claimed "C" document published after the international filling date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.			
Date of the a	actual completion of theinternational search	Date of mailing of the international sear	
15	January 1998	28/01/1998	
Name and m	ailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Fay: (-31-70) 340-3016	Authorized officer	

INTERNATIONAL SEARCH REPORT

Inter mal Application No PCT/PL 97/00023

	Note that to claim No.				
Category °	Onation of Goodinam, with indication, where appropriate, or the relevant passages	rielevalit to claim No.			
(DE 27 21 212 A (D. HLAWATSCH) 16 November 1978 see page 5, paragraph 3 - page 11,	1,2			
	paragraph 3				
		,			
	·				
	•				
	·				
		·			
	•				
	*				
	•				

INTERNATIONAL SEARCH REPORT

...formation on patent family members

Inter: nal Application No PCT/PL 97/00023

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
DE 9300198 U	18-03-93	NONE	-	
GB 2270464 A	16-03-94	NONE		
FR 2147406 A	09-03-73	NONE		
US 5546625 A	20-08-96	NONE		
DE 2721212 A	16-11-78	NONE		